

Key Features

- Ultra Fine Touch Technology offering up to 40-point touch for a penon-paper writing experience
- myViewBoard Whiteboard software with engaging classroom tools
- Screen share via USB-C or wirelessly via myViewBoard Display and ViewBoard Cast with Airplay and Chromecast
- Intuitive remote device control and multimedia broadcast with myViewBoard Manager
- Android 11 OS powered by an octa-core CPU for optioptimised efficiency and security (Upgradable to Android 13)



Product **Description**

Designed with modern educators in mind, the ViewBoard® 50-5F Series offers an intuitive and interactive interface for a multi-user writing experience. With a single-cable USB-C for instant, worry-free connectivity, teachers can seamlessly plug-in and control their devices while continuing the lesson. Both students and educators enjoy smooth writing with Ultra Fine Touch Technology offering 40-point touch, and the dual-pen that comes in a range of colours and sizes. Rest assured you and your students' eyes are cared for and protected as the ViewBoard® 50-5F Series comes with Flicker-Free technology and an integrated TÜV certified blue light filter for all brightness levels. Fully integrated with the myViewBoard suite, the ViewBoard® 50-5F Series brings together hardware and software for a complete classroom solution. Compatible with a full line of accessories, the ViewBoard® 50-5F Series enables you to effectively teach with a variety of engaging tools.







www.viewsonic.com

DISPLAY

EMBEDDED OS

		ENIBEDDED 03	
Panel Size:	75"	Android 11 (upgradable to Android	13)
Panel Type:	TFT LCD Module with	BUNDLE SOFTWARE	
raner rype.	DLED Backlight. IPS	Basic Annotation Software:	myViewBoard
Display Area (mm):	1650.24(H) × 928.26(V)	Pro Annotation Software:	myViewBoard for Windows (Embedded in
Aspect Ratio:	16:9		Windows Slot-in PC)
Resolution:	UHD 3840x2160	Wireless Presentation:	vCast/myViewBoard Display App
Colors:	1.07B colors (10bit)	SPECIAL FEATURES	
Brightness:	500 nits	All-in-one USB port:	"SmartPort™ USB" to
Contrast Ratio:	1200:1 (typ.) 6000:1 (DCR)	Simple LAN sharing between IFP	all channels. Yes
Response Time:	8ms	and slot-in device:	100
Viewing Angles:	H = 178, V = 178 typ.	Light Sensor:	Yes
Backlight Life:	50,000 hours(Min)	POWER	
Surface Treatment:	Hardness: 7H, Anti- glare coating	Voltage:	100-240VAC +/- 10% Wide Range
Bezel:	Slim	Consumption:	124W(typ.), 0.5W (off)
Orientation:	Landscape	ERGONOMICS	
Disclaimer:	50,000 hours backlight life at 8 hours of use per day	Wall Mount (VESA®):	800 mm x 400 mm
		OPERATING CONDITIONS	
PLATFORM	po	Temperature (°C):	0°C to 40°C
Processor:	ARM Cortex-A73*4 + Cortex-A53*4	Humidity:	10% ~ 90% RH non- condensing
RAM:	8GB	DIMENSIONS (W X H X D)	
Storage:	64GB	Physical (inch / mm):	67.3 x 40.2 x 3.5 in / 1710 x 1020 x 90 mm
тоисн		Packaging (inch / mm):	76.0 x 44.9 x 11.0 in /
Type/ Tech:	Ultra Fine Touch Techology (IR Recognition)		1930 x 1140 x 280 mm
		WEIGHT Net (lb / kg):	118.8lb/53.9kg
Touch Resolution:	32768 ×32768	Gross (lb / kg):	158.5lb/71.9kg
Touch Point:	Windows: 40 points of touch, Android : 20 points of touch	REGULATIONS cTUVus, FCC/ICES003, Energy Star 8.0, EMC/CE,	
INPUT		CB/LVD, GOST-R/EAC, UkrSEPRO, EPEAT, Mexico NOM, Mexico Energy, UKCA, UK-EEL, BSMI, BIS, LBL(Low Blue	
HDMI:	2.0 x 3 (3840x2160 @60Hz, HDCP2.2, HDMI1 with CEC/ARC)	Light Certification), Flicker Free, Green BOM, RoHS, ErP- Eco, REACH, SCIP, WEEE, TPCH , Packing waste, CA65, PAIA	
RS232:	x1	PACKAGE CONTENTS	
OPS:	x1	1. Power cord	
WiFi:	x 1 module slot	2. Remote control with AAA battery	
OUTPUT		3. Touch USB cable	
HDMI:	x1 (4K@60Hz)	4. Touch pen x 2	
Audio:	x1 (Earphone out)	(VB-PEN-009)	
SPDIF:	x1 (optical)		
LAN		5. Quick Start Guide + Compliance statement	
RJ45:	x2	6. RS232 adapter	
USB		7. Clamp x 5	
Туре А:	2.0 x 2 3.0 x 4	8. Camera Plate	
Туре В:	x2, for touch	9. Screw x 8	
ט פּקעי.		10. HDMI cable	
Туре С:	x1 (DP 1.2, USB2.0, PD65W, Ethernet 100M)		
		 VPC25-W33-O1-1B VPC25-W53-O1-1B 	

SPEAKERS

20W x 2 + 20W x 1 subwoofer

TOP CAMERA PLATE

Yes

Copyright © ViewSonic Corporation 2000-2024. All rights reserved.

• VPC27-W53-O1-1B

• VPC27-W55-O2-1B