

SB603

Flat Panel Display Soundbar



SB603



Flat Panel Display Soundbar

60W

60w speaker
output



Wall mount kit
included



APT[™]
Bluetooth



Remote control
included

The SB603 is a high efficiency, high output power audio solution that delivers excellent value for money and is the perfect complement to interactive whiteboards or interactive flat panels.

Ideally suited to the education and corporate environments where high definition audio is a must-have and with no need for a separate subwoofer, the ConXeasy SB603 has two built-in Ultra-Bass passive drivers, two bass drivers and two full range drivers, allowing full frequency range audio in a single discrete unit. Comes with a three year warranty.

Key to the SB603 is its connectivity - it can easily connect to any panel or audio source via cable (analogue or digital), HDMI or wirelessly via Bluetooth meaning that audio can be streamed from a laptop or smartphone or tablet.



ConXeasy[™]

SB603

Flat Panel Display Soundbar

ConXeasy™ SB603

Flat Panel Display Soundbar

The SB603 features a TOSLINK optical input, analogue input, Bluetooth aptX® input, as well as two HDMI inputs and one HDMI output. The HDMI output features Audio Return Channel (ARC), which means it can also function as an input. In addition, the Bluetooth aptX® functionality brings added convenience to the application - providing for lossless, high quality streaming audio from smartphones, laptops and tablets. The presence of this codec makes the SB603 unique in its product category.



Specifications

INPUTS

Bluetooth : A2DP audio using either SBC & APTX™ decoders
3.5mm stereo mini-jack : 500 mV RMS full scale input
Optical : SPDIF format, Toslink compatible, Stereo only, Up to 96 KHz sample rate at up to 24 bit PCM data
HDMI x 2

OUTPUTS

HDMI (ARC) x 1

AMPLIFIERS

Class-D power-stages.
2x10W capability@<10% THD+N
2x20W capability@<10% THD+N
3 DSP Settings (Hall, Music, Speech)

SPEAKERS

Mid-High Range : 2 x 2.75" Ferrite Drivers
Bass: 2 x 2.75" Ferrite Drivers
2 x Passive Bass Radiators

PERFORMANCE

Output power (RMS @ THD<10%) : 60W
Frequency response : 70 Hz - 15K Hz
Dynamic Signal Processing : Speech / Hall / Music

DISPLAY & CONTROL

Display Type : LCM , 16 characters x 2 line
Remote Control keys : ON/OFF, MUTE, VOL+, VOL-, INPUT, SPEECH, HALL, MUSIC

AC POWER

External 19V 3.42A (65W) 220/110 AC input
Power Requirements: AC 230 - 240V ~ 50Hz

DIMENSIONS

900 x 85 x 88 mm (W, D, H)

WHAT'S IN THE BOX

Soundbar with Wall Mount Kit and Remote Control
3.5mm to 3.5mm Aux Cable (1m), Optical Cable, HDMI Right-Angle Adapter



Just Projectors,
Unit 7,
Campbell Court,
Bramley,
Hampshire,
RG26 5EG

ConXeasy™